



Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 20156 PM XERAMIC Ceramic Paste Pressurepack
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Petromark Automotive Chemicals

Rooswijkweg 316, 1951 ME Velsen-Noord, The Netherlands

www.petromark.eu • info@petromark.eu

Tel. +31 (0)251 211397

· Further information obtainable from:

Petromark Automotive Chemicals: info@petromark.eu

· 1.4 Emergency telephone number:

Petromark Automotive Chemicals: Tel. +31 (0)251 211397

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 3 H229 Pressurised container: May burst if heated.

- · 2.2 Label elements
- \cdot Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

H229 Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Additional information:

Safety data sheet available on request.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 2)





Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

(Contd. of page 1)

1 - 2.5%

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture: consisting of the following components: mineral oil, lubricant, and additives

· Dangerous	components:
-------------	-------------

CAS: 811-97-2 1,1,1,2-tetrafluoroethane substance with a Community workplace exposure limit

Reg.nr.: 01-2119459374-33-xxxx

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Personal protection for the First Aider.

Take affected persons out into the fresh air.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. Remove contact lenses, if present and easy to do. Continue rinsing. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

CO2, powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Nitrogen oxides (NOx)

In case of fire, the following can be released:

Carbon monoxide (CO)

Danger of bursting by heating.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 3)



Page 3/9

Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

(Contd. of page 2)

Cool endangered receptacles with water spray and remove it out of emergency area if possible.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

· Information about fire - and explosion protection:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- \cdot Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location under dry conditions in well sealed receptacles

Observe official regulations on storing packagings with pressurised containers.

Do not store in gangways or stairways.

· Information about storage in one common storage facility:

Do not store together with oxidizing and selfigniting materials.

· Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Do not store together with oxidizing and selft-igniting material.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)





Revision: 08.06.2016 Printing date 08.06.2016 Version number 1

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

(Contd. of page 3)

· 8.1 Control parameters

o.i Control parameters				
· Ingredients with limit values that require monitoring at the workplace:				
811-97-2 1,1,1,2-tetrafluoroethane				
WEL (Great Britain) Long-term value: 4240 mg/m³, 1000 ppm				
· DNE	· DNELs			
811-97-2 1,1,1,2-tetrafluoroethane				
Inhalative wrks, long, system		13936 mg/m³ (mouse)		
cstm, long, system		2476 mg/m³ (mouse)		
· PNECs				
811-97-2 1,1,1,2-tetrafluoroethane				
Oral	fresh water	0.1 mg/l (daphnia)		
	sediment (fresh water)	0.75 mg/(kg dw) (daphnia)		
	STP	73 mg/l (daphnia)		
	marine water	0.01 mg/l (daphnia)		

- 1.0 mg/l (daphnia) · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:

intermittent release

- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

Short term filter device:

Filter P2

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing





Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

(Contd. of page 4)

9.1 Information on basic physical a	and chemical properties
General Information	• •
Appearance:	
Form:	paste-like
Colour: Odour:	Whitish
Odour threshold:	Weak, characteristic Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	275 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Vapour pressure:	Not applicable.
Density at 20 °C:	1.26 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Kinematic:	Not determined.
VOC (EC)	0.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.
- · 10.3 Possibility of hazardous reactions Danger of bursting.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products occur when handling in accordance with the rules.

No decomposition if used according to specifications.



Page 6/9

Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	· European waste catalogue		
13 00 00	OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19)		
13 02 00	waste engine, gear and lubricating oils		
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils		
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST		
16 05 00	gases in pressure containers and discarded chemicals		
16 05 04*	gases in pressure containers (including halons) containing hazardous substances		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
	(Contd. on page 7		

(Contd. on page 7)





Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

	(Contd. of page 6)
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging

- Uncleaned packaging:
 Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport inform	utton
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, non-flammable
· 14.3 Transport hazard class(es)	
· ADR	
2	
· Class	2 5A Gases.
· Label	2.2
· Class	2.2
· Label	2.2
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity abo
	1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

(Contd. on page 8)





Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

	(Contd. of page
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS
	Segregation as for the appropriate subdivision of class 2.
• 14.7 Transport in bulk according to An	
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	3
· Tunnel restriction code	E
	(Dangerous goods in "LQ" with more than 8 tons gros
	mass of LQ falls under the tunnel restriction code "E")
· IMDG	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.2

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ctsm, long, system: general population, long-term exposure, systematic effects

cstm, short, system: general population, acute / short-term exposure, systematic effects

wrks, long, system: workers, long-term exposure - systemic effects

wrks, short, system: workers, acute / short-term exposure - systemic effects

cstm, long, local: general population, long-term exposure, local effects

STP: sewage treatment plant

(Contd. on page 9)



Page 9/9

Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016 Version number 1 Revision: 08.06.2016

Trade name: 20156 PM XERAMIC Ceramic Paste - Pressurepack

(Contd. of page 8)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Aerosol 3: Aerosols – Category 3

 \cdot * Data compared to the previous version altered.

GB ·