

Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 20325 PM Xeramic® Glass Cleaner Foam

· Article number: 20325

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

• Product category PC35 Washing and cleaning products (including solvent based products)

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Application of the substance / the mixture Surface active agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Petromark Automotive Chemicals

Rooswijkweg 316, 1951 ME Velsen-Noord, The Netherlands

www.petromark.eu info@petromark.eu Tel. +31 (0)251 211397

· Further information obtainable from:

Petromark Automotive Chemicals: info@petromark.eu

· 1.4 Emergency telephone number:

Petromark Automotive Chemicals, Tel. +31 (0)251 211397

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

(Contd. on page 2)



Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

(Contd. of page 1)

5 - 15%

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Active substance with propellant

· Dangerous components:		
EINECS: 203-905-0	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas C, H280	2.5-<10%
CAS: 1336-21-6 EINECS: 215-647-6	ammonia Skin Corr. 1B, H314; Aquatic Acute 1, H400	0.25-<1%

· Ingredients according to detergents guidline 648/2004/EC aliphatic hydrocarbons

· Additional information:

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

(Contd. of page 2)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

WEL | Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)



Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

(Contd. of page 3)

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)



Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

(Contd. of page 4)

SECTION 9: Physical	and chemical	properties
----------------------------	--------------	------------

0 1 T P 1				4 •
· 9.1 Information	on hacic	nhveical ai	nd chamical	nronorfice
7.1 IIIIVI IIIauvii	on pasic	pirysicar a	nu chemica	properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

• **pH-value at 20 °C:** 10

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 0 °C

· Flash point: -60 °C

· **Self-igniting:** Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 1.1 Vol % **Upper:** 10.6 Vol %

· Vapour pressure at 20 °C: 23 hPa

Density at 20 °C: 0.96 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 10.7 % **Water:** 88.4 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

(Contd. of page 5)

· LD/LC50 values relevant for classification:		
111-76-2 2-butoxyethanol		
Oral		300 mg/kg (rabbit)
		470 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eve damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

111-76-2 2-butoxyethanol

LC50 1490 mg/l (Lepomis macrochirus (96 h))

- · 12.2 Persistence and degradability Easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

14 1 IIN Number

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number	
· ADR, ADN, IMDG, IATA	UN1950

· 14.2 UN proper shipping name

· ADR, ADN UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 7)



Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases.
Label	2.1
ADN	
ADN/R Class:	2 5F
IMDG, IATA	
2	
Class	2.1
Class Label	2.1 2.1
	
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Segregation groups	Alkalis
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity above
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a
	capacity above 1 litre: Segregation as for the appropriat
	subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
Transport category	Not permitted as Excepted Quantity 2
Tunnel restriction code	D D
IMDG	
IMDG Limited quantities (LQ)	1L
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity



Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

(Contd. of page 7)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

Class	Share in %
Wasser	75-<100
NK	10-<25

- · VOC-CH 10.70 %
- · VOC-EU 102.7 g/l
- · Danish MAL Code 3-1
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

- · Department issuing SDS: Research & Development
- · Contact: info@petromark.eu
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

(Contd. on page 9)





Printing date: 24.10.2016 Version: 15 Revision: 24.10.2016

Trade name: 20325 PM Xeramic® Glass Cleaner Foam

(Contd. of page 8)

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

- * * Data compared to the previous version altered. *